Specifications for PPK based drone with RBG, Multispectral and Thermal sensors:

1. Technical specifications for drone:

	Parameters	Range
01.	Category	: Small category Quadcopter
02.	Operational range	: ≥ 5 Km
03.	Flight endurance time	At least 45 Minutes
04.	Flight speed	. ≥ 20m/s.
06.	Operating Altitude	: ≥ 100m above ground level
07.	Net weight including payload	≥ 4Kg
09.	PPK enabled with internal	Yes
	storage	
10.	RGB Sensor/camera module	Yes
11.	Flight management software	: Yes
12.	DGCA Approved	: Yes
13.	NPNT Approved	Yes
14	Make in India	· Ves

2. Technical Specification for thermal camera/sensor:

	Parameters	Range
01.	Field of View	: 32°
02.	Measuring Spectral band range	: 7.5-13.5 μm
03.	Operating temperature range	: -10°C to + 50°C
04.	Operational Height	: ≥ 100m
06.	Capture/Frame Rate	: 7.5 Hz
07.	Weight	: ≤ 250 grams
08.	Nominal Power Consumption	: ≤ 4 W

3. Technical Specification for multispectral camera/sensor:

	Parameters	Range
01.	Field of View	: ≥ 45°
02.	Spectral bands	Blue, Green, Red, Red edge, near IR
03.	Capture/Frame Rate	1 capture per second
04.	Weight	: ≤ 250 grams
05.	Nominal Power Consumption	: ≤ 4 W

4. Software required:

- a. For Post processing (3D reconstruction)
 - i. Spatial aerial triangulation,
 - ii. Dense Cloud orthorectification and mosaic creation,
 - iii. Digital terrain model,
 - iv. 3D modeling
- b. For Photogrammetry analysis with capabilities of
 - i. Image processing & Georeferencing
 - ii. Geospatial Analysis
 - iii. Multispectral and hyperspectral image processing

5. Must include rugged tablet for ground control station with loaded necessary software for flight planning and data acquisition.

6. Spare propellers, batteries, charging unit and other peripherals with a carrying case must be

included.

7. Onsite training of all modules/components must be done within 15 days post-delivery. Two weeks training at laboratory and at field site of landslide in hilly terrain must be given by the supplier.